



Government of Andhra Pradesh

**COMMON SCHEDULE OF RATES
AS PER
A.P. REVISED STANDARD
DATA FOR THE YEAR 2020-21
(Effective from 1st June, 2020)**

BOARD OF CHIEF ENGINEERS

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2020-21 (Rs.)
1		2	3	4	5
			manufacturers specification and direction of Engineer-in-Charge for finished item of work		
674	MAT-01334	BMT-N.05	SINGLE SIDE PRELAM SOLID PANEL PVC DOOR FRAME (CHOUKHAT): Providing and fixing factory made Pac single side Prelam door frame of the size 50X47 mm with a wall thickness of 5mm, made out of extruded 5mm rigid Pac single side prelam sheet, meter cut at two corners and joined with 2nos. of 150mm long brackets of 1515mm MS.Square tube. The two vertical door profiles are to be reinforced with 19X19mm MS. square tube of 19guage. The door frame shall be fixed to the wall using 65/100mm long MS. Screws through the frame by using Pac fasteners. a minimum of 4nos. of screws to be provided for each vertical member and minimum 2nos. for horizontal member etc. complete as per manufacture specification and direction of Engineer-in-charge.	1 Rm	330
675	MAT-01361	BMT-N.32	Supply and fixing of door frame made of hollow extruded PVC section having dimensions of 40 X 57mm with the wall thickness of 2mm +/- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be metri-cut/ welded. PVC DOOR FRAME	1 RM	237
676	MAT-01362	BMT-N.33	Supply and fixing of door frame made of hollow extruded PVC section having dimensions of 40 X 46 mm with the wall thickness of 2mm +/- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be mitre cut/welded	1 RM	186
677	MAT-01363	BMT-N.34	Supply & fixing of Door frames made of all formed sections of 1.25mm thick CRCA section, size should be 50x60mm with 32mm rebate. The corner of the frame should be welded. The frame should be painted with one coat of primer and finished painted with pure polyester paint. The frame should be provided with approved quality butt hinges of 3 Nos. complete for finished item.: Single shutter 3'-0" x 7'-0" (914.4x2133.6mm) outer frame section size of 50 x 60 mm	1RM	197

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2020-21 (Rs.)
1		2	3	4	5
			PVC strip of 20 mm width stuck on the interior side of the C channel using solvent cement, complete as per direction of Engineer-in-charge, manufacturers specification.		
732	MAT-01382	BMT-N.53	Supplying & fixing SINGLE PANEL 30 mm thick PVC DOOR, door shutters with shutter frame and Infill panel made from PVC material, the shutter frame made out of PVC extruded sections having overall dimensions of 60mm x 30 mm with wall thickness of 1.3 mm ± 0.3 mm, with the Infill panel made out of multi chambered seamless hollow PVC extruded panel having overall dimensions of 610 mm x 20 mm having wall thickness 1 mm ± 0.2 mm with the shutter frame meter cut and joined at corners and all the hardware locations reinforced with special polymeric bars as per drawing including providing special PVC bracket on hinge side, etc complete	1 Sqm	2350
733	MAT-01384	BMT-N.55	Supply & Fixing of Powder Coated Mild Steel doors, frames & shutters made of Skin pass galvanized Iron sheet conforming to Base Steel as per IS 513 "D" Quality, Galvanized as per IS 277 with Hot Zinc Coating of 120 grams / Sq.Mtr with powder coating of thickness 60-65 Microns, frame with 1.2mm thick Skin pass Galvanized Iron sheet formed to single rebate profile of size 100 mm X 58 mm and filled with in-fill Polyurethane foam, the Door Shutters are with 0.80 mm thick Skin pass Galvanized Iron Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper and coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns and are coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, the Shutter provided with 6 MM clear float vision glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter	1 Sqm	9902

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2020-21 (Rs.)
1		2	3	4	5
			0.45mm on the vertical sides. Hardware made out of steel coated butterfly hinges - 3 Nos. for each shutter and ISI make S.S round lock completes for finished item of work. Maximum shutter size of : 910 x 2030 mm		
743	MAT-01398	BMT-N.69	Supply and fixing of Bath room / Toilet door shutter with 16mm laminated (IS 14276) door shutter with all-round 'U' lipping of PPS section of size 12mm X 18mmX 12mmX0.6mm thickness with a hardware of 12mm dia X200mm long aluminum aldop – 2 nos(ISI make)2 No of 125mm long handles(ISI make) and also 3 no Of IS304 grade Patee Hinges 3mmX12mmX180mm long with pole receiver of 10mm dia pole X40mm long welded on 2mm X40mm(ss304) plates works as receiver for RT patte hinges. The price inclusive of all material at site	1 Sqm	2265
744	MAT-01399	BMT-N.70	Supply and fixing of toilet door shutter with frame made of M.S. door frame of 5mmX48mmX48mm (L angel) as all-round frame the frame is coated with one coat of red oxide and two coats of enamel of approved color. For shutter and the shutter is made with 16mm laminated shutter with all-round 'U' Lipping of PPS section of 12mmX18mmX12mmX0.60mm, along hardware of 200m long and 12mm dia aluminum aldop(ISI make)2 Nos, 2Nos of 125m m handle, 3 Nos of RT patte hinges IS 304gr SS 2mmX12mmX180mm long with a pole receiver of 10mmDia X 40mm by welded on 3mmX40mm SS 304, plate it works as receiver for RT Patee hinges it is welded to M.S. angle . M.S. angle will be fixed to wall of self expandable screws and caps.	1 Sqm	3230
745	MAT-01402	BMT-N.73	Door shutter with shutter frame and Infill panel made from PVC material conforming to IS: 10151:1982. The shutter frame is made out of PVC extruded sections having overall dimensions of 100mm X 30mm, with two self extruded grooves at 40mm & 50mm on front surface. The Infill panel is made out of multi chambered seamless hollow PVC extruded panel having overall dimensions of 610 mm X 20 mm. The shutter frame shall be meter cut and	Sqm.	960

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2020-21 (Rs.)
1		2	3	4	5
			joined at corners by means of plastic brackets. Stickers showing locations of different hardware will be pasted on the shutter. ALL Dimensions are in MM.		
746	MAT-01403	BMT-N.74	The shutter frame made out of PVC extruded section having overall dimensions of 59mm x 24mm with wall thickness of 1.0mm +/-0.3mm with usual process variation corresponding to the Sintex Code No.DWUF-302. The shutter frame is given tapered shape to provide better grip to the infill panel and to drain out the water.The infill panel is made out of seamless one piece multi chambered PVC extruded section having overall dimension of 610mm x 20mm with wall thickness of 1mm +/-0.2mm with usual process variation corresponding to the Sintex code No.SPUF-128. The shutter frame shall be mitre cut and joined at the corner polymeric "L' Type corners shall be provided at the corners to take up hardwares & fixtures and shall be fixed with 19 x 8mm counter sunk-fully threaded parallel shank steel screws. All the hardware locations shall be reinforced with special polymeric Bars.	1 Sqm	1924
747 to 750		BMT-N.75 to BMT-N.78	ITEMs DELETED		
751	MAT-01338	BMT-N.09	Providing and fixing PVC door cladding to the flush doors shutters . For the new doors it shall be pasted with Fevicol SSR 998 or nailed to the old doors. complete as per direction of Engineer – in – charge, manufacturers specification and drawing - 1 mm thick	1 sqm	350
752	MAT-01339	BMT-N.10	Providing and fixing PVC door cladding to the flush doors shutters . For the new doors it shall be pasted with Fevicol SSR 998 or nailed to the old doors. complete as per direction of Engineer – in – charge, manufacturers specification and drawing - 1.5 mm thick	1 sqm	375
753	MAT-01340	BMT-N.11	Providing and fixing PVC door cladding to the flush doors shutters . For the new doors it shall be pasted with Fevicol SSR 998 or nailed to the old doors. complete as per direction of Engineer – in – charge, manufacturers specification and drawing - 2.0 mm thick	1 sqm	431
754		BMT-N.84	Providing and fixing factory made uPVC		